

(11)

**● PRINTER RUSH ●**  
**(PTO ASSISTANCE)**

Application : <u>10/670226</u>	Examiner : <u>Duden</u>	GAU : <u>2871</u>
From : <u>J. Black</u>	Location : <u>IDC</u> FMF FDC	Date : <u>5/11/05</u>
Tracking # : <u>06091519</u>		Week Date : <u>4/4/05</u>

DOC CODE	DOC DATE	MISCELLANEOUS
<input type="checkbox"/> 1449	_____	<input checked="" type="checkbox"/> Continuing Data
<input type="checkbox"/> IDS	_____	<input type="checkbox"/> Foreign Priority
<input type="checkbox"/> CLM	_____	<input type="checkbox"/> Document Legibility
<input type="checkbox"/> IIFW	_____	<input type="checkbox"/> Fees
<input type="checkbox"/> SRFW	_____	<input type="checkbox"/> Other
<input type="checkbox"/> DRW	_____	
<input type="checkbox"/> OATH	_____	
<input type="checkbox"/> 312	_____	
<input type="checkbox"/> SPEC	_____	

**[RUSH] MESSAGE:**

Please update form to show "371 OF PCT/JP96/02562"  
under Continuing data.

Thank you!

**[XRUSH] RESPONSE:**

OK

**INITIALS:** JB

## **ACTIVE-MATRIX LIQUID CRYSTAL DISPLAY**

### **CROSS REFERENCE TO RELATED APPLICATION**

This is a continuation of U.S. application Serial No. 09/904,835, filed July 16, 2001 and U.S. application Serial No. 09/029,747, filed March 2, 1998, now U.S.

5 Patent No. 6,266,117, which is a 371 of PCT/JP96/102562, filed September 9, 1996, the subject matter of which is incorporated by reference herein.

### **FIELD OF THE INVENTION**

The present invention relates to an active-matrix liquid crystal display device, and particularly to a liquid crystal display device of the so-called in-plane field type.

### **10 BACKGROUND OF THE INVENTION**

In color liquid crystal display devices of the in-plane field type, one or both of two transparent substrates placed opposite to each other, with a liquid crystal layer disposed in between, have display electrodes and reference electrodes arranged in areas on the sides of the liquid crystal corresponding to unit pixels, and an electric  
15 field parallel to the transparent substrate surface is produced between the display electrodes and the reference electrodes to modulate light passing through the liquid crystal layer.

Such a color liquid crystal display device can produce a picture that can be recognized at a wide viewing angle and has become known for its excellence in the  
20 so-called wide angle visual field.

Liquid crystal display devices with the above configuration are described in detail, for example, in the Published Japanese Translation of PCT International Publication for Japanese Patent Application No. 505247/1993, Japanese Patent Publication No. 21907/1988, and Japanese Patent Laid-Open No. 160878/1994.

25 It has been pointed out that liquid crystal display devices of this configuration, however, have a problem in that an undesired electric field produced from the video signal line changes the electric field between the display electrodes and the